

Beyond Attendance *PF-X*

The PF-X is the latest device to be offered in the Beyond Attendance stable. The unit is available in three different configurations:

1. Facial Only
2. Facial + Palm
3. Facial + Palm + Thermal

The thermal option allows for early warning of anyone running a temperature and is able to alert select people immediately.

Built with world leading hardware and making use of state of the art finger print and facial recognition algorithms, this device is ideal for almost any application as its accurate, secure and reliable.

Features :

- Composite algorithm system with high speed operating
- Embedded LINUX system, easy to integrate into various system
- Support Access Control
- Standalone or network environment
-
- 65,000 real colour display, menu with high-definition graphical user interfaces
- Huge capacity memory with high speed verification supports user photos display
- Saves data during power outage
- 24 hours continuous operation available
- Prevents buddy clocking
- Push Firmware



Display / Speaker	Language
LCD Display 8" TFT high-definition touch interface	English
Speaker: Voice Prompt	
Technical Specification Capacity	Environment
Facial Capacity 30, 000 RFID Card Capacity 5 0, 000	Ops temp: 0°C–45°C
Log Capacity 100,000	Ops Humidity: 10-60%
Verification / Identification	
Verification Speed: Approx. 0.3s	FPR <0.01%
Identification Speed: Approx. 01s	FAP < 0.0001%
Power Supply	Machine Size
110/220VAC–12VDC	227 * 143 * 26mm
Communication	Attendance Status
TCP/IP, RS232, USB, Wiegand In/ Out, Speaker Out	Check In, Check Out, Break In, Break Out, OT In, OT Out
Standard Function	Custom Function
Professional access control, built-in relay, 50 time zones, 5 groups and 10 combinations, dismantlement alarm, break-in alarm, duress alarm; User-defined function key; Auto DST; Scheduled bell, SMS, T9 input, Webserver, Work code; Photo-ID; power lock; Anti-pass back; Self service query; Keypad audio	9-PIN ID, Multi-verify, Group identify; Printer output,, ID reader, Mifare reader

